

HD 10C VV

Tandem roller with two vibrating roller drums

Tandem rollers Series HD CompactLine / Series H263





HIGHLIGHTS HD CompactLine

- > Simple, intuitive and language-neutral operation
- > Easy transport, simple loading
- > Ergonomic driver platform
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Compact dimensions

Machine dimensions		
Total length (L)	mm	2295
Width (B)	mm	1080
Total height (H)	mm	2210
Drum width (X)	mm	1000/1000
Height loading, min. (Hl)	mm	1580



EU Stage V /
EPA Tier 4

TECHNICAL DATA		Unit	HD 10C VV
	Weights		
	Operating weight with ROPS	kg	1670
	Operating weight, max.	kg	1950
	Static linear load, front/rear	kg/cm	8,1/8,6
	French classific., data/class		8,6/PV2
	Machine dimensions		
	Total length	mm	2295
	Total height with ROPS	mm	2210
	Height loading, min.	mm	1580
	Wheel base	mm	1560
	Total width	mm	1080
	Max. working width	mm	1064
	Turning radius, inside	mm	2130
	Drum dimensions		
	Drum width, front/rear	mm	1000/1000
	Drum diameter, front/rear	mm	620/620
	Drum thickness, front/rear	mm	12/12
	Drum type, front		Smooth/non-split
	Drum type, rear		Smooth/non-split
	Diesel engine		
	Manufacturer		KUBOTA
	Version		D1105
	Number of cylinders		3
	Power rat. ISO 14396, kW/PS/rpm		16,8/22,9/2600
	Power rating SAE J1349, kW/HP/rpm		16,8/22,5/2600
	Emission standard		EU Stage V / EPA Tier 4
	Exhaust gas after-treatment		-
	Drive		
	Speed, infinitely variable	km/h	0 - 11,0
	Climbing ability, vibration on/off	%	30/40
	Vibration		
	Vibration frequency, front, I/II	Hz	65/52
	Vibration frequency, rear, I/II	Hz	65/52
	Amplitude, front, I/II	mm	0,45/0,45
	Amplitude, rear, I/II	mm	0,45/0,45
	Centrifugal force, front, I/II	kN	25/16
	Centrifugal force, rear, I/II	kN	25/16
	Steering		
	Oscillation angle +/-	°	8
	Steering, type		Articulated steering
	Sprinkler system		
	Water sprinkler, type		Pressure
	Tank capacity/Fill capacity		
	Fuel tank, capacity	L	33
	Water tank, capacity	L	70
	Sound level		
	Acoustic power LW(A), sticker		104
	Acoustic power LW(A), measured		103

EQUIPMENT

12 V socket, 3-point articulation, Dashboard with displays, indicator lights and switches, Dashboard cover, lockable and weather-resistant, Clear Side, Pressure water sprinkling with interval switch, Operator's platform with entry from both sides, V-belt protection, Automatic vibration system, Water filtering (triple), Central lifting bracket

OPTIONAL EQUIPMENT

Plastic scraper, foldable, ROPS, foldable, Additional drive lever, left, Anti-freeze injection system, Automatic engine-off function, Back-up alarm (reversing), Working lights, Rotating beacon, Cup holder, , Water drain valve, Additional mirror

HAMM AG
Hammstraße 1
D-95643 Tirschenreuth
Tel +49 9631 80-0
Fax +49 9631 80-111
www.hamm.eu



HAMM