

# HD 10 VO

Tandem roller with vibrating roller drum and oscillation drum

Tandem rollers Series HD CompactLine / Series H262









## HIGHLIGHTS HD CompactLine

- > Simple, intuitive and language-neutral operation
- > Ergonomic driver platform
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Compact dimensions
- > Compaction with oscillation

Machine dimensions		
Total length (L)	mm	2530
Width (B)	mm	1110
Total height (H)	mm	2475
Drum width (X)	mm	1000/1000
Height loading, min. (HI)	mm	1752



TECHNICAL DATA		Unit	HD 10 VO
	<b>Weights</b>		
	Operating weight with ROPS	kg	2525
	Operating weight, max.	kg	3240
	Static linear load, front/rear	kg/cm	12,1/13,2
	French classific., data/class		13,2/PV3
	<b>Machine dimensions</b>		
	Total length	mm	2530
	Total height with ROPS	mm	2475
	Height loading, min.	mm	1752
	Wheel base	mm	1700
	Total width	mm	1110
	Max. working width	mm	1050
	Kerb clearance, left/right	mm	570/570
	Turning radius, inside	mm	2470
	<b>Drum dimensions</b>		
	Drum width, front/rear	mm	1000/1000
	Drum diameter, front/rear	mm	720/720
	Drum thickness, front/rear	mm	15/15
	Drum type, front		Smooth/non-split
	Drum type, rear		Smooth/non-split
	Track offset, left/right	mm	0/50
	<b>Diesel engine</b>		
	Manufacturer		KUBOTA
	Version		D1503
	Number of cylinders		3
	Power rat. ISO 14396, kW/PS/rpm		22,9/31,1/2700
	Power rating SAE J1349, kW/HP/rpm		22,9/30,7/2700
	Emission standard		EU Stage IIIA
	Exhaust gas after-treatment		-
	<b>Drive</b>		
	Speed, infinitely variable	km/h	0-12,0
	Climbing ability, vibration on/off	%	35/40
	<b>Vibration</b>		
	Vibration frequency, front, I/II	Hz	67/52
	Amplitude, front, I/II	mm	0,54/0,54
	Centrifugal force, front, I/II	kN	46/28
	<b>Oscillation</b>		
	Oscillation force, rear, I/II	kN	40/23
	Oscillation frequency, rear, I/II	Hz	39/30
	Tangential amplitude, rear, I/II	mm	1,34/1,34
	<b>Steering</b>		
	Oscillation angle +/-	°	8
	Steering, type		Articulated steering
	<b>Sprinkler system</b>		
	Water sprinkler, type		Pressure
	<b>Tank capacity/Fill capacity</b>		
	Fuel tank, capacity	L	42
	Water tank, capacity	L	180
	<b>Sound level</b>		
	Acoustic power LW(A), sticker		106
	Acoustic power LW(A), measured		104

#### EQUIPMENT

12 V socket, 3-point articulation, Dashboard with displays, indicator lights and switches, Dashboard cover, lockable and weather-resistant, Pressure water sprinkling with interval switch, Operator's platform with entry from both sides, Drive lever, left and right, Vibration-isolated operator's platform, Track offset, mechanical, Automatic vibration system, Water filtering (triple), Central water drain, Central lifting bracket, ROPS, rigid

#### OPTIONAL EQUIPMENT

Plastic scraper, foldable, Edge pressing and cutting equipment, Track indicator, Chip spreader, Thermal aprons, All-wheel lock, Anti-freeze injection system, HAMM Compaction Meter (HCM), HAMM Temperature Meter (HTM), Working lights, Drum edge lighting, Water drain valve, Tow eye, at the front, Tow hitch, V-belt protection

**HAMM AG**  
Hammstraße 1  
D-95643 Tirschenreuth  
Tel +49 9631 80-0  
Fax +49 9631 80-111  
www.hamm.eu

